

LS Pro 9500 MID: Non-Contact Length & Speed Measurement System

Intelligent, compact non-contact linear encoder with highest accuracy in accordance with European Directive MID

A breakthrough in electro-optics design enables the LaserSpeed® Pro 9500 MID series encoder to produce highly accurate, reliable non-contact length and speed measurements. Coupled with the Beta LaserMike DataPro 1000 MID display, the LS Pro 9500 MID system is certified according to the high standards of the European Measuring Instruments Directive (MID). This approval has been granted by the Czech Metrology Institute (CMI) in 2021 according to Modules B and D under Directive 2014/32/EU.

The LaserSpeed Pro series encoders have no moving parts, use 100% solid-state digital technology, and are permanently calibrated resulting in significant time and money savings. An integrated and enhanced version of autocorrelation, along with an Acousto-Optical modulator, gives the LaserSpeed Pro 9500 series the capability to measure forward and reverse directions and zero speed (no motion). All LaserSpeed Pro series encoders deliver better than $\pm 0.03\%$ accuracy to meet the Class 1 status of the EU Directive ($\pm 0.125\%$).

The MID policy was agreed upon in April 2004 and covers a number of measuring instrument types, including gas and electricity meters, petrol pumps, and automatic weighing instruments. The primary aim of the Directive is to create a single market in measuring instruments for the benefit of manufacturers and ultimately consumers across Europe.

From this date forward, only MID-certified systems will be accepted. Older systems, such as devices with no measurement traceability or ones that have been in long-term storage, will no longer be valid. The LaserSpeed Pro 9500 MID system meets all EU requirements. It is an ideal replacement for mechanical-type encoders (tachometers) that can lose contact on product surfaces due to slippage, vibration, and debris build-up and provide erroneous measurements, and cause damage to material. Our Accredited Customer Services offer installation support for LaserSpeed Pro 9500 MID systems and provide effective communication with the certifying authorities to simplify the transition process.



Benefits

- ▶ High accuracy and repeatability
- ▶ Direct replacement for tachometers
- ▶ No moving parts to wear out
- ▶ Permanently calibrated
- ▶ Low cost of ownership
- ▶ Measures forward and reverse directions and zero speed (no motion)
- ▶ Provides long-term data storage with traceability of measured values
- ▶ Non-contact length and speed measurement
 - No slippage
 - Not affected by material surface or color
 - Non-marking

Range of Applications

LS Pro gauges are well suited for a range of applications, including, but not limited to, measuring length and speed of:

- ▶ Wire, cable, and optical cable
- ▶ Rubber tube and hose
- ▶ Paper and corrugated products
- ▶ Plastic pipe and tube
- ▶ Web products
- ▶ Plastic films and tapes
- ▶ Non-woven products
- ▶ Building materials

Accessories

- ▶ **Guide Rollers/Height Stand**
Various guides and height stand options are available for standard applications.
- ▶ **Laser Safety Enclosure**
Protects operators from direct or indirect laser beam exposure. Meets the EU laser safety requirements.



LS Pro 9500-4XX MID	-403	-406
Standoff Distance	300 mm (12 in.)	600 mm (24 in.)
Speed Range	0 to ±2000 m/min (0..±6,560 ft/min)	0 to ±2000 m/min (0..±6,560 ft/min)
Measurement Depth of Field	35 mm (1.4 in.)	50 mm (2 in.)

LS Pro 9500-4 MID (Continuous Length/Speed Measurement)

Accuracy	±0.125% of reading (instrument accuracy better than ±0.03%)	Controller Power	- 120/240 @ 4 Amp (including Gauge)
Repeatability	±0.02%	Spot Size	- 3 x 5 mm
Measurement Rate	100,000/s	Gauge Size	203 X 159 X 95.2 mm (8.0 X 6.3 X 3.75 in.)
Acceleration Rate	>500 m/s ²	Gauge Weight	3.4 kg (7.5 lbs)
Status via Serial I/O (Gauge)	- Laser at Temperature - Laser On - Shutter Open - Valid Measurements	Ambient Temperature	5 to 40°C (41 to 104°F) Cooling/heating is required for temperatures outside this range
Serial I/O (Controller) Data Available	- RS-232 ,Ethernet - Length, Length Report - USB Printer port	Relative Humidity	Non-condensing 65%
Serial Baud Rate	- 1200, 2400, 4800, 9600, 19.2K	Degree of Protection	IP67 (Gauge) IP54 (Controller)
Status via Serial I/O (Controller)	- Length - Date - Time	Units of Measure	- m/min
		Product Warranty	2 years
		Diode Warranty	5 years

Specifications are subject to change without notice.

Inputs		
Input	Description	Details
1	End of Reel Report	Prints the Date, Time & current length to the USB printer port
2	Transmit Length	Outputs the Date, Time & current length over RS-232
3	Transmit Length Report	Outputs the Date, Time, Machine Number, Product Number & current length over RS-232
4	Transmit Stored Data	Transmit the stored flash memory data (last 90 days) over the EtherNet port
5	Length Reset	Resets the current length

Outputs				
Control Output Type	Length Measurement Mode			
	Relay 1	Relay 2	Relay 3	Relay 4
Relay Closure	Preset Length Reached	-Preset Length Approach	Quality Factor Warning	Quality Factor Reject

This unit is a class 3B laser product and Complies with IEC/EN60825-1:2014. Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.



The following safety features required to comply with the Bureau of Radiological Health Class IIIB laser requirements are included:

- Key-operated power switch on optional controller
- Laser indicator light on supply and laser
- Delayed laser startup-laser indicator light on prior to laser radiation
- Laser beam blocking device
- Interlock capability for remote shut-off

NDC Technologies is represented in over 60 countries worldwide. www.ndc.com/betalasermike

NDC Americas
Tel: +1 937 233 9935
Email: info@ndc.com

NDC China
Tel: +86 21 6113 3617
Email: ndcchina@ndc.com

NDC Germany
Tel: 08001123194
Email: ndcgermany@ndc.com

NDC India
Tel: +91 9971232913
Email: ndcindia@ndc.com

NDC United Kingdom
Tel: +44 1621 852244
Email: ndcuk@ndc.com

NDC Japan
Tel: +81 3 3255 8157
Email: ndcjapan@ndc.com

NDC Italy
Tel: +39 0331 454 207
Email: ndcitaly@ndc.com

NDC South Korea
Tel: +65 9296 0881
Email: ndcapac@ndc.com

In line with its policy of continuous improvement, NDC reserves the right to revise or replace its products or services without prior notice. The information contained in this document may not represent the latest specification and is for indicative purposes only.

Document #: C&T-BROC-SCAN-LaserSpeed_MID-EN-2022APR19
Date of Issue: April 2022
© NDC Technologies 2022

Intelligence that transforms the world.